SNSHN FIVE DEPARTURE (RNAV)

(SNSHN5.SNSHN) 10SEP20

ONTARIO, CALIFORNIA
ONTARIO INTL (ONT)

D-ATIS
124.25
CLNC DEL
118.1
CPDLC
GND CON
121.9 257.8
ONTARIO TOWER
120.6 360.775
SOCAL DEP CON
125.5 349.0

NOTE: RNAV 1.
NOTE: RADAR required.
NOTE: DME/DME/IRU or GPS required.
NOTE: Turbojet and turboprop aircraft only.
NOTE: MISEN transition restricted to aircraft landing LAS terminal area.
NOTE: HAILO/BEALE/YELAH transition ATC only.
NOTE: Maintain at or below 250K unless otherwise directed by ATC.

TOP ALTITUDE: FL230

COREZ
SHAFTER EHF
MDWAY
SHORS
TUNAY
LIVVI 14000
GUNNR
ARRMY
HAILO
NNAVY
MISEN
BLAZN
WYZEE
BEALE
LAS VEGAS LAS
YELAH
ARCUS
XBBOX 17000
BROOQ 12000
NLAND 14000
SNSHN
POMONA POM 8000
DINNK
LEESI 5000

16000 317° (40)
16000 319° (64)
16000 318° (12)
14000 295° (51)
14000 300° (24)
10500 016° (8)
15000 073° (16)
15000 044° (55)
15000 035° (53)
15000 035° (117)
15000 035° (51)
15000 042°
15000 043° (19)
15000 035° (63)
15000 036° (40)
15000 036° (44)
15000 036° (75)
15000 038° (29)
15000 058° (26)
15000
8900 307° (11)
8700 293° (17)
300° (4)
(4) 274°
285° (8)
1460 258°
078° 1460 210K

N

TAKEOFF MINIMUMS
Rwys 8L/R, 26L/R: Standard with minimum climb of 500′ per NM to 1460, then a minimum climb of 400′ per NM to 11200.

(NARRATIVE ON FOLLOWING PAGE)

NOTE: Chart not to scale.

(SNSHN5.SNSHN) 20254
SNSHN FIVE DEPARTURE (RNAV)
AL-965 (FAA)
ONTARIO INTL (ONT)
ONTARIO, CALIFORNIA