

APP CRS  
171°

Rwy Idg  
TDZE  
Apt Elev

4000  
288  
309

RNAV (GPS) RWY 17

ANVIK (ANV)(PANV)

▼

⚠

❄

-32°C

DME/DME RNP-0.3 NA. When local altimeter setting not received, use Holy Cross altimeter setting and increase all MDAs 120 feet and LNAV visibility Cat C ¼ mile, Cat D ½ mile.

MISSED APPROACH: Climbing left turn to 3700 direct OYASA and hold, continue climb-in-hold to 3700.

AWOS-3P 133.55	ANCHORAGE CENTER 135.7 335.5	KENAI RADIO 122.4	UNICOM 122.7 (CTAF) 0
-------------------	---------------------------------	----------------------	--------------------------

The main enroute chart displays a series of waypoints and flight paths. Key features include:

- OYASA**: Initial approach fix with distances of 30 NM to OYASA (NoPT) at 5100 and 1.5 NM to OYASA at 3700. Heading 081° to 262°.
- TICUR**: Intermediate approach fix with distances of 30 NM to TICUR at 4800 and 10 NM to TICUR at 3700. Heading 081° to 351°.
- SEBEE**: (FAF) Fix at 2400.
- VUPLY**: Fix at 2900.
- PACKI**: Final approach fix with distances of 18 NM to PACKI at 3700 and 30 NM to PACKI at 4200. Heading 351° to 262°.
- NOTIE**: (MAP) Fix at 366±.
- Altitudes**: Various altitudes are marked along the path, including 1575, 1710, 2400, 2900, and 3700.
- Headings**: Key headings include 081°, 171°, 262°, and 351°.

ELEV 309

TDZE 288

35

4000 X 7.5

1

MIRL Rwy 17-35 1

REIL Rwy 17 and 35 1

3700

OYASA

VGSI and descent angles not coincident (VGSI Angle 3.00/TCH 25).

NOTIE

SEBEE

VUPLY

PACKI

4 NM Holding Pattern

3700

CATEGORY	A	B	C	D
LNAV MDA	700-1	412 (400-1)	700-1½	412 (400-1½)
CIRCLING	840-1	543 (600-1)	840-1½	860-2

ANVIK, ALASKA

Orig-A 26MAY16

62°39'N-160°11'W

RNAV (GPS) RWY 17

ANVIK (ANV)(PANV)