

WAAS CH 82010 W05A	APP CRS 053°	Rwy Idg TDZE Apt Elev	8002 666 668
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 5

MBS INTL (MBS)

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C (0°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. For inoperative ALS, increase LNAV/VNAV all Cats visibility to RVR 4500 and LNAV Cats C/D visibility to RVR 6000.
** RVR 1800 authorized with use of FD or AP or HUD to DA.

MALSR

MISSED APPROACH:
Climb to 2300 direct
FOROX and hold.

ATIS 125.925	GREAT LAKES APP CON★ 126.45 235.625	SAGINAW TOWER ★ 120.1(CTAF) 257.7	GND CON 121.7	CLNC DEL 121.85	UNICOM 122.95
------------------------	---	---	-------------------------	---------------------------	-------------------------

4 NM Holding Pattern					2300 FOROX
GP 3.00° TCH 50					*1.1 NM to RW05 *LNAV only.
CATEGORY					
LPV DA**					866/24 200 (200-½)
LNAV/ VNAV DA					955/24 289 (300-½)
LNAV MDA					1080/24 414 (500-½) 1080/40 414 (500-¾)
CIRCLING					1080-1 412 (500-1) 1120-1 452 (500-1) 1240-1½ 572 (600-1½) 1240-2 572 (600-2)

SAGINAW, MICHIGAN
Amdt 2 01FEB18

43°32'N - 84°05'W

MBS INTL (MBS)

RNAV (GPS) RWY 5