

APP CRS
116°

Rwy Idg
TDZE
Apt Elev

4304
869
869

RNAV (GPS) RWY 11

LUCE COUNTY (ERY)

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 47°C (116°F). DME/DME RNP-0.3 NA. Visibility reduction by helicopters NA. When local altimeter setting not received, use Chippewa Co Intl altimeter setting and increase DA 105 feet and all MDA 120 feet, increase LNAV/VNAV visibility ¼ mile all Cats, LNAV Cats C and D ½ mile, and Circling Cats C and D ¼ mile. Baro-VNAV NA when using Chippewa Co Intl altimeter setting.

MISSED APPROACH:

Climb to 2700 direct
DIHZE and hold.

AWOS-3 119.525	MINNEAPOLIS CENTER 134.6 354.05	UNICOM 122.8 (CTAF) 0
--------------------------	---	---------------------------------

4 NM Holding Pattern

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 50).

2700 DIHZE

* LNAV only.

GP 3.00° TCH 40

2700 2500 2300 1640

6.1 NM 2.6 NM 2.3 NM

CATEGORY	A	B	C	D
LNAV/VNAV DA	1259-1½ 390 (400-1½)			
LNAV MDA	1360-1 491 (500-1)	1360-1¼ 491 (500-1¼)	1360-1½ 491 (500-1½)	
CIRCLING	1360-1 491 (500-1)	1360-1½ 491 (500-1½)	1420-2 551 (600-2)	

ELEV 869 TDZE 869

116° to RW11

4304 X 75

0.4% UP

2836 X 150

MIRL Rwy 11-29 0

REIL Rwy 11 and 29 0

NEWBERRY, MICHIGAN

Orig-A 07APR11

46°19'N - 85°27'W

LUCE COUNTY (ERY)

RNAV (GPS) RWY 11