

WAAS  
CH **40340**  
**W35A**

APP CRS  
**346°**

Rwy Idg **3503**  
TDZE **665**  
Apt Elev **665**

**RNAV (GPS) RWY 35**

ONTONAGON COUNTY - SCHUSTER FIELD (OGM)

Baro-VNAV NA.

Rwy 35 helicopter visibility reduction below ¾ SM NA.

DME/DME RNP-0.3 NA. Use Hancock altimeter setting.

MISSED APPROACH: Climb to 1300 then climbing right turn to 3700 direct PELTZ and hold, continue climb-in-hold to 3700.

CMX ASOS <b>125.675</b>	MINNEAPOLIS CENTER <b>133.55 379.1</b>	CTAF <b>122.9 0</b>
----------------------------	---	------------------------

The main chart displays the RNAV (GPS) RWY 35 approach. Key features include:

- Obstacles:** A 1860± ft obstacle near the start, and a 1700 ft obstacle near the final approach.
- Navigation Aids:** RW35, KAGRE (2.3 NM to RW35), (FAF) RUUGS, (IF/IAF) BINGR, (IAF) COTMO, and (IAF) LAUU.
- Altitudes:** 1300, 1560, 1660, 2600, 3460, and 3700 ft.
- Angles:** 346° to RW35, 166° to 3700, and 346° to 2600.
- MSA:** Minimum Safe Altitude (MSA) for RW35 is 3200 ft within 25 NM.
- Procedures:** Procedure NA for arrivals at PELTZ on V148 northeast bound, and Procedure NA for arrivals at COTMO on V316 westbound.

ELEV 665

TDZE 665

1300

3700

PELTZ

\*LNAV only.

RW35

KAGRE 2.3 NM to RW35

\*1560

2600

346°

166°

3700

GP 3.50° TCH 40

CATEGORY	A	B	C	D
LPV DA	1152-1½ 487 (500-1½)			NA
LNAV/VNAV DA	1301-1⅞ 636 (700-1⅞)			NA
LNAV MDA	1280-1	615 (700-1)	1280-1¾ 615 (700-1¾)	NA
CIRCLING	1320-1	655 (700-1)	1420-2¼ 755 (800-2¼)	NA

MIRL Rwy 17-35 0

REIL Rws 17 and 35 0

ONTONAGON, MICHIGAN

Orig 17AUG17

ONTONAGON COUNTY - SCHUSTER FIELD (OGM)

46°51'N-89°22'W

**RNAV (GPS) RWY 35**