RNAV (GPS) RWY 25

FINDLAY (FDY)

WAAS	APP CRS	Rwy Idg	4558
CH 56405	254°	TDZE	812
W25A		Apt Elev	813

RNP APCH

T For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 47°C. Baro-VNAV and VDP NA when using Lima Allen County altimeter setting. When local altimeter setting not received, use Lima Allen County altimeter setting: increase all DAs/MDAs 80 feet; increase LPV visibility ⅛ SM all Cats; increase LNAV Cat C/D and Circling Cat C/D visibility ¼ SM.

MISSED APPROACH: Climb to 2500 direct PURIC and hold.

ASOS	TOLEDO APP CON	UNICOM
132.85	120.8 317.55	122.725 (CTAF) L



2500 | PURIC

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 31).

4 NM Holding Pattern



ELEV 813 D TDZE 812



HIRL Rwys 7-25 and 18-36 L
REIL Rwys 7, 25 and 36 L

CATEGORY	A	B	C	D
LPV DA	1116-1 304 (400-1)			
LNAV/VNAV DA	1411-2 599 (600-2)			
LNAV MDA	1280-1 468 (500-1)		1280-1⅜ 468 (500-1⅜)	1280-1½ 468 (500-1½)
CIRCLING	1440-1 627 (700-1)		1440-1¾ 627 (700-1¾)	1440-2 627 (700-2)

EC-2, 31 DEC 2020 to 28 JAN 2021
EC-2, 31 DEC 2020 to 28 JAN 2021