

APP CRS
319°

Rwy Idg
7801

TDZE
439

Apt Elev
459

RNAV (GPS) RWY 32L

SCOTT AFB/MIDAMERICA (BLV)

NA

ASR

DME/DME RNP-0.3 NA. For inoperative ALSF-1, increase LNAV Cat C/D visibility to 1½ mile.

ALSF-1

MISSED APPROACH: Climb to 1500 then climbing left turn to 2400 direct QODCU and hold.

ATIS ★ 128.7 256.7	ST LOUIS APP CON 125.2 281.5	SCOTT TOWER 128.25 253.5	GND CON 119.2 275.8	CLNC DEL 119.875 225.4 263.025
-----------------------	---------------------------------	-----------------------------	------------------------	-----------------------------------

The main chart illustrates the RNAV (GPS) RWY 32L approach. Key features include:

- MSA RW32L 25 NM:** A circular Minimum Safe Altitude (MSA) with a radius of 25 NM and a center altitude of 2700 feet.
- Arrival from DUTMY:** A procedure NA for arrival at DUTMY on V44 southeast bound. The path starts at 2400 feet (239°/17.6°), passes through a 4 NM segment, and then turns to 319°/39°.
- Arrival from NEWAT:** A procedure NA for arrival at NEWAT on V234 southwest bound. The path starts at 2400 feet (023°/9.4°) and turns to 319°.
- Intermediate Points:** The path includes points (FAF) TIZGE at 2100 feet and (IF) QODCU at 2100 feet.
- Final Approach:** The path continues from QODCU to RW32L at 499± feet, then to 871 feet, and finally to 834 feet.
- Obstacles:** Obstacles are marked with their MSL altitudes: 834, 499±, 871, 597, 1155, and 660±.

ELEV 459

TDZE 439

REIL Rwy 14L
HIRL Rwy 14R-32L and 14L-32R

1500

2400

QODCU

VGSI and descent angles not coincident (VGSI Angle 3.00/TCH 50).

QODCU

Profile view showing the descent from 2400 feet to 2100 feet (3.03° TCH 55) and then to 1500 feet. Distances are marked: 1.3 NM to RW32L, 3.7 NM to TIZGE, and 5 NM to QODCU.

CATEGORY	A	B	C	D
LNAV MDA	920/24	481 (500-½)	920/50	481 (500-1)
CIRCLING	1000-1 541 (600-1)	1080-1 621 (700-1)	1240-2¼ 781 (800-2¼)	1240-2½ 781 (800-2½)

BELLEVILLE, ILLINOIS

Orig-E 26MAY16

38°33'N-89°50'W

SCOTT AFB/MIDAMERICA (BLV)

RNAV (GPS) RWY 32L