

WAAS

CH **60909**

**W29A**

APP CRS

**291°**

Rwy Idg

**6525**

TDZE

**871**

Apt Elev

**871**

**RNAV (GPS) RWY 29**

CENTRAL IL RGNL ARPT AT BLOOMINGTON-NORMAL (BMI)

▼

▲

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. Baro-VNAV and VDP NA when using General Downing-Peoria Intl altimeter setting. When local altimeter setting not received, use General Downing-Peoria Intl altimeter setting: increase all DA 116 feet and all MDA 120 feet; increase LPV all Cats visibility to RVR 3500, LNAV/VNAV all Cats and LNAV Cats C/D visibility ¾ mile, and Circling Cats C/D visibility ¼ mile. For inoperative MALSRs when using General Downing-Peoria Intl Regional altimeter setting increase LPV all Cats visibility ½ mile, and LNAV Cat C/D visibility ¾ mile.

MALSR

MISSED APPROACH:  
Climb to 2500 direct ZEXED and hold.

ATIS <b>135.35</b>	PEORIA APP CON <b>128.725 256.9</b>	BLOOMINGTON TOWER ★ <b>124.6 (CTAF) 269.575</b>	GND CON <b>121.65</b>	UNICOM <b>122.95</b>
-----------------------	--	--	--------------------------	-------------------------

Procedure NA for arrivals at JILLY via V173 northeast bound and V227 northwest bound.

Procedure NA for arrivals at EWITT via V313 southbound and V233 southwest bound.

ELEV 871

D

TDZE 871

TDZ/CL Rwy 20

HIRL Rwy 2-20 and 11-29

2500 ZEXED				
*LNAV only				
*1.6 NM to RW29				
CATEGORY	A	B	C	D
LPV DA	1121/24 250 (300-½)			
LNAV/VNAV DA	1304/50 433 (500-1)			
LNAV MDA	1460/24	589 (600-½)	1460-1¼	589 (600-1¼)
CIRCLING	1460-1	589 (600-1)	1620-2¼ 749 (800-2¼)	1620-2½ 749 (800-2½)

BLOOMINGTON/NORMAL, ILLINOIS

Amdt 1A 15OCT15

CENTRAL IL RGNL ARPT AT BLOOMINGTON-NORMAL (BMI)

40°29'N-88°55'W

**RNAV (GPS) RWY 29**