

APP CRS	Rwy Idg	6506
182°	TDZE	407
	Apt Elev	411

RNAV (GPS) RWY 18L

SOUTHERN ILLINOIS (MDH)


▼

⚠

Inoperative table does not apply to LNAV Cat D. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 48°C (118°F)

DME/DME RNP-0.3 NA. When local altimeter setting not received, use Williamson Co Rgnl altimeter setting and increase all DA 36 feet and all MDA 40 feet and increase LNAV/VNAV Cat A, B, C visibility ¼ mile. For inoperative MALSR, increase LNAV/VNAV Cat D visibility to 1 mile. Baro-VNAV NA when using Williamson Co Rgnl altimeter setting. VDP NA when using Williamson Co Rgnl altimeter setting. For inoperative MALSR when using Williamson Co Rgnl altimeter setting, increase LNAV Cat D visibility to 1¼ mile.

MALSR




MISSED APPROACH: Climb to 2700 direct SOPAW and hold.

ATIS 119.725	KANSAS CITY CENTER 127.475 346.275	CARBONDALE TOWER ★ 125.35 (CTAF) 0 322.4	GND CON 121.8	UNICOM 122.95
-----------------	---------------------------------------	---------------------------------------------	------------------	------------------

ELEV 411 D TDZE 407

182° to RWY 18L





HIRL Rwy 18L-36R


MIRL Rwy 6-24


MIRL Rwy 18R-36L


REIL Rws 6, 24 and 36R


 473±


 4163 X 100


 494

 464

 6506 X 100

 3498 X 60

 36L

 36R

2700	SOPAW	HEMPA	4 NM Holding Pattern
*LNAV only	*0.9 NM to RWY 18L	JOROB	002° 2700
RWY 18L	2100	182°	GP 3.00° TCH 55°
0.9	4.2 NM	6 NM	
CATEGORY	A	B	C
LNAV/VNAV DA	726-½	319 (400-½)	726-¾ 319 (400-¾)
LNAV MDA	740-½	333 (400-½)	740-1 333 (400-1)
CIRCLING	900-1	489 (500-1)	900-1½ 489 (500-1½)
			980-2 569 (600-2)

CARBONDALE-MURPHYSBORO, ILLINOIS

Orig 08APR10

SOUTHERN ILLINOIS (MDH)

37°47'N-89°15'W

RNAV (GPS) RWY 18L