



WAAS CH 70505 W22A	APP CRS 221°	Rwy Idg TDZE 1500 Apt Elev 1500
--	------------------------	---

RNAV (GPS) RWY 22

JAMESTOWN RGNL (JMS)

<div><div></div><div></div></div> <div>For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -21°C (5°F) or above 54°C (130°F). DME/DME RNP- 0.3 NA.</div>		MISSED APPROACH: Climb to 3700 direct GANEY and hold.
ASOS 118.425	MINNEAPOLIS CENTER 124.2 270.3	UNICOM 123.0 (CTAF) 0



3700

↑

GANEY

✦

VGSI and RNAV glidepath not coincident

(VGSI Angle 3.00/TCH 21).

DOLEC

1.9 NM to RW22

ENUSE

3300

CALOT

4 NM Holding Pattern

*LNAV only

*1.1 NM to RW22

221°

2140*

041° →

← 221°

3300

GP 3.00°

TCH 45

1.1 NM

0.9 NM

3.6 NM

6 NM

RW22

3300

CATEGORY	A	B	C	D
LPV DA	1750-¾ 250 (300-¾)			
LNAV/VNAV DA	1790-1 290 (300-1)			
LNAV MDA	1860-1 360 (400-1)			
CIRCLING	1960-1	460 (500-1)	2000-1½ 500 (500-1½)	2300-2½ 800 (800-2½)