

## ILS or LOC RWY 31

LOC R-YM

111.1

Chan 48

APCH CRS

312°

Rwy Idg

TDZE

Arprt Elev

6100

1146

1150

AL-5226 [USA]

RAY S. MILLER AAF (KRYM)

When local altimeter setting not received, use Little Falls altimeter setting.

MALSF

A4

MISSED APPROACH: Climb to 2000, then climbing left turn to 3500 direct XCR NDB and hold. Continue climb in hold to 3500.

MINNEAPOLIS CENTER

118.05 239.0

MILLER TOWER ★

126.2 0 254.4 46.7

CLNC DEL

126.2

to XCR 3500 -072° (37.9)

ALEXANDRIA 112.8 AXN Chan 75

LOCALIZER 111.1 I-RYM Chan 48

Procedure NA when R-4301 is active.

R-4301

1547 A

132°

3300 132° to PEGGO (5.8)

1680 A

1289 (IAF) PEGGO I-RYM 7.5

087°

267°

312°

URHIL

NaPT

3200

3300

3500

132°

2.1.8

SAINT CLOUD 112.1 STC Chan 58

ELEV 1150

TDZE 1146

TWR

Assault Strip

1299

312° 6.3 NM from FAF

312°

3300

3500

2.5 NM

MSA XCR

312°

3300

3500

2.5 NM

MSA XCR

ADF and DME REQUIRED

RADAR REQUIRED

(For procedure entry at STC VOR/DME)

2000

3500

XCR

LOC Only

PEGGO 7.9

5000

132°

312°

3300

3200

GS 3.00° TCH 40

2.5 NM

3.8 NM

1.2

2.4

1344

1980

I-RYM DME

VDP NA with Little Falls altimeter setting.

ZAKPI 3.7

MM

Remain within 10 NM of PEGGO

CATEGORY

A

B

C

D

S-ILS 31

1346-1

200

(200-1)

S-LOC 31

1580-1

434

(500-1)

CIRCLING

1640-1 490 (500-1)

1660-1 510 (600-1)

1720-1½ 570 (600-1½)

2080-3 930 (1000-3)

LITTLE FALLS ALTIMETER SETTING MINIMUMS

S-ILS 31

1370-1

224

(300-1)

S-LOC 31

1620-1 474 (500-1)

1620-1½ 474 (500-1½)

CIRCLING

1680-1 530 (600-1)

1700-1 550 (600-1)

1760-1¾ 610 (700-1¾)

2120-3 970 (1000-3)

HIRL Rwy 13-31

0