LOC RWY 36

JOHNSON COUNTY EXECUTIVE (OJC)

LOC I-PKX	APP CRS	Rwy Idg	4098
108.3	356°	TDZE	1086
		Apt Elev	1096

T NA — Helicopter visibility reduction below ¾ SM not authorized. For inoperative MALSRs, increase S-36 Cats A and B visibility ¼ mile.

MALSR

MISSED APPROACH: Climb to 1700 then climbing right turn to 2700 direct HERBB LOM and hold.

ATIS	KANSAS CITY APP CON	EXECUTIVE TOWER ★	GND CON	UNICOM
119.35	118.9 251.075	126.0 (CTAF) L 225.4	121.6	122.95

MSA PK 25 NM
3100

KANSAS CITY
113.25 MCI
Chan 79 (Y)

3000 to LOM
176°
(31.9)

2044

ADF REQUIRED

LOCALIZER 108.3
I-PKX

1254±

ALTERNATE MISSED APCH FIX
R-319
139°
NAPOLEON
ANX
114.0
Chan 87
319°

LOM/IAF
HERBB
420 PK

176°
356°
131°
311°
(CFBXV)
2700 to LOM
331°
(31.1)
176°

BUTLER
115.9 BUM
Chan 106

ELEV 1096 TDZE 1086
MIRL Rwy 18-36 L

18
1151
TWR
1157
4098 X 75
1.1% UP
V
A5
36

356° 5.3 NM from FAF

Remain within 10 NM
PK LOM
176°
2700
356°
2700
2.85°
TCH 40
5.3 NM

1700	2700	PK

FAF to MAP 5.3 NM

Knots	60	90	120	150	180
Min:Sec	5:18	3:32	2:39	2:07	1:46

CATEGORY	A	B	C	D
S-36	1580-¾ 494 (500-¾)		1580-1 494 (500-1)	NA
C CIRCLING	1620-1 524 (600-1)		1620-1½ 524 (600-1½)	NA

NC-2, 31 DEC 2020 to 28 JAN 2021
NC-2, 31 DEC 2020 to 28 JAN 2021