

WAAS
CH **93804**
W18A

APP CRS
176°

Rwy ldg
TDZE **1277**
Apt Elev **1277**

RNAV (GPS) RWY 18

WELLINGTON MUNI (E/GT)

RNP APCH.

▼

▲NA

Baro-VNAV and VDP NA when using Wichita Dwight D Eisenhower National altimeter setting.
For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C.
When local altimeter setting not received, use Wichita Dwight D Eisenhower National altimeter setting: increase LPV DA to 1531 feet; increase LNAV/VNAV DA to 1776 feet; increase all MDAs 60 feet and LNAV Cats C/D visibility ½ SM and Circling Cats C/D visibility ¼ SM.

MISSED APPROACH:
Climb to 3000 direct
GOTPE and hold.

AWOS-3
118.875

WICHITA APP CON
134.85

UNICOM
122.8 (CTAF) 0

4 NM Holding Pattern

TANUC

HUMUN 3000

UDEYE 1.8 NM to RW18

*1880

*1.2 NM to RW18

RW18

GP 3.00° TCH 40

6 NM 3.5 NM 0.6 NM 1.2 NM

CATEGORY A B C D

LPV DA	1477-1 200 (200-1)			
LNAV/VNAV DA	1722-1 3/8 445 (500-1 3/8)			
LNAV MDA	1700-1 423 (500-1)	1700-1 1/4 423 (500-1 1/4)		
CIRCLING	1760-1 483 (500-1)	2040-2 1/4 763 (800-2 1/4)	2140-2 3/4 863 (900-2 3/4)	

HIRL Rwy 18-36 0

REIL Rwy 18 and 36 0

NC-2, 31 DEC 2020 to 28 JAN 2021

NC-2, 31 DEC 2020 to 28 JAN 2021