

WAAS CH 86407 W15A	APP CRS 146°	Rwy Idg TDZE 1162 Apt Elev 1165
--	------------------------	---

RNAV (GPS) RWY 15


NEBRASKA CITY MUNI (AFK)

RNP APCH

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. When local altimeter setting not received, use Omaha altimeter setting and increase all DA 122 feet and all MDA 140 feet, and increase LPV Cat A/B visibility ¼ SM and LNAV/VNAV Cat A/B visibility ½ SM.

MISSED APPROACH: Climb to 3000 direct OJEKE and hold.

AWOS-3PT 128.325	OMAHA APP CON 120.1 354.05	UNICOM 122.7 (CTAF) 0
----------------------------	--------------------------------------	---------------------------------



4 NM Holding Pattern

3000 ← 326°
146° →

GP 3.00°
TCH 52

JUPMO

IGUSE

RW15

3000

OJEKE

*LNAV only

*1.2 NM to RW15

6.3 NM

3.7 NM

1.2 NM

CATEGORY	A	B	C	D
LPV DA	1412-1	250 (300-1)		NA
LNAV/VNAV DA	1539-1¼	377 (400-1¼)		NA
LNAV MDA	1580-1	418 (500-1)		NA
CIRCLING	1640-1	475 (500-1)		NA

