

APP CRS	Rwy Idg	10552
123°	TDZE	540
	Apt Elev	618

RNAV (RNP) Z RWY 12R

ST LOUIS LAMBERT INTL (STL)

For uncompensated Baro-VNAV systems, procedure NA below -16°C (4°F) or above 54°C (130°F). GPS required. For inop ALS, increase RNP 0.30 all Cats visibility to 1½ SM. Simultaneous approach authorized with Rwy 11 except for arrivals at RRIIP and HRBEE. Use of FD or AP required during simultaneous operations.

MALSR

MISSED APPROACH: Climb to 5000 on track 123° to FONTI and hold, continue climb-in-hold to 5000.

D-ATIS	ST. LOUIS APP CON	ST. LOUIS TOWER	GND CON	CLNC DEL	CPDLC
125.025	132.125 360.6	118.5 257.7	121.9 348.6 (Inbound)	119.5 363.1	
379.925			121.65 377.175 (Outbound)		
			118.925 227.125 (Rwy 11/29)		

ELEV 618

TDZE 540

123° to RWY 12R

Rwy 6-24 7607 X 150

Rwy 11-29 9001 X 150

Rwy 12L-30R 9003 X 150

Rwy 12R-30L 11019 X 200

HIRL all Rwys

REIL Rwy 12L

TDZ/CL Rwys 11, 12L, 12R, 29, and 30R

HOPWD

See planview for multiple IF locations.

GP 3.00°

TCH 54

CATEGORY	A	B	C	D
RNP 0.30 DA	998/60 458 (400-1¼)			

AUTHORIZATION REQUIRED

ST. LOUIS, MISSOURI

Orig-C 29MAR18

38°45'N-90°22'W

ST LOUIS LAMBERT INTL (STL)

RNAV (RNP) Z RWY 12R