

19171

RNAV (GPS) Y RWY 12R
ST LOUIS LAMBERT INTL (STL)

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. For inop ALS, increase LPV Cat E visibility to RVR 4000, LNAV Cat A/B visibility to RVR 5000, and LNAV Cat E visibility to 1½ SM. Inop table does not apply to LNAV/VNAV. Simultaneous approach authorized with Rwy 11. LNAV procedure NA during simultaneous operations. Use of FD or AP required during simultaneous operations.

MISSED APPROACH:
Climb to 5000 direct
FONTI and hold,
continue climb-in-hold
to 5000.

Figure 1 illustrates a 4th step climb profile. The profile starts at 4500 ft and descends in steps to 1000 ft. Key waypoints include PAULY, NAIRN, TUDNE, and FONTI. The profile is divided into segments A, B, C, D, and E. Segment A is from 4500 to 3600 ft, segment B is from 3600 to 2400 ft, segment C is from 2400 to 2000 ft, segment D is from 2000 to 1500 ft, and segment E is from 1500 to 1000 ft. The profile is labeled '4th step climb profile' and '4th step climb profile'.

ST LOUIS LAMBERT INTL (STL)
RNAV (GPS) Y RWY 12R

NC-3, 31 DEC 2020 to 28 JAN 2021