WAAS	APP CRS	Rwy Idg	5000
CH 82019	024°	TDZE	890
W02A		Apt Elev	892

RNAV (GPS) RWY 2

NEVADA MUNI (NVD)

NA

DME/DME RNP-0.3 NA. Baro-VNAV and VDP NA when using Joplin Rgnl altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 54°C (130°F). When local altimeter setting not received, use Joplin Rgnl altimeter setting and increase all DA 112 feet and all MDA 120 feet, increase LNAV/VNAV all Cats and LNAV Cat C visibility ¼ mile. Circling NA to Rwy 13-31.

MISSED APPROACH: Climb to 3000 direct STARE and hold.

AWOS-3	KANSAS CITY CENTER	UNICOM
119.175	125.55 327.0	122.8 (CTAF) L



ELEV 892	TDZE 890

MIRL Rwy 2-20 L

REIL Rwys 2 and 20 L





CATEGORY	A	B	C	D
LPV DA	1090-1 200 (200-1)			NA
LNAV/VNAV DA	1219-1¼ 329 (400-1¼)			NA
LNAV MDA	1220-1 330 (400-1)			NA
CIRCLING	1260-1 368 (400-1)	1440-1 548 (600-1)	1440-1½ 548 (600-1½)	NA

NC-3, 31 DEC 2020 to 28 JAN 2021
NC-3, 31 DEC 2020 to 28 JAN 2021