RNAV (GPS) RWY 35

PLATTSBURGH INTL (PBG)

WAAS	APP CRS		
CH **78003**	**353°**	Rwy Idg	**11759**
W35A		TDZE	**177**
		Apt Elev	**234**

T A

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C (0°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. For inop MALSR, increase LPV and LNAV/VNAV all Cats visibility to ⅞ mile. For inop MALSR when using Burlington altimeter setting, increase LPV and LNAV/VNAV all Cats visibility to 1 mile. When local altimeter setting not received, use Burlington altimeter setting and increase all DA 54 feet and all MDA 60 feet; increase LPV and LNAV/VNAV all Cats visibility to ⅝ mile, LNAV Cats C, D visibility to 1¼ mile, and increase Circling Cats C/D visibility ¼ mile. VDP and Baro-VNAV NA when using Burlington Intl altimeter setting.

MALSR

MISSED APPROACH: Climb to 3500 direct OTGOE and hold, continue climb-in-hold to 3500.

ASOS	BURLINGTON APP CON ★	CLNC DEL	UNICOM
132.225	**121.1 278.8**	**121.85**	**122.7** (CTAF) L







CATEGORY		A	B	C	D
LPV	DA	427-½ 250 (200-½)			
LNAV/VNAV	DA	434-½ 257 (200-½)			
LNAV	MDA	700-½ 523 (500-½)		700-1 523 (500-1)	
C	CIRCLING	720-1 486 (600-1)	740-1 506 (600-1)	800-1½ 566 (700-1½)	960-2¼ 726 (800-2¼)

NE-2, 31 DEC 2020 to 28 JAN 2021
NE-2, 31 DEC 2020 to 28 JAN 2021