CAMP SPRINGS, MARYLAND

ILS RWY 19R (CAT III)

JOINT BASE ANDREWS (KADW)

LOC I-MXK	APCH CRS	Rwy Idg	9318
111.5	190°	TDZE	274
		Arpt Elev	280

AL-561 [USAF]

ATC RADAR or DME required.

ALSF-2

† MISSED APPROACH: Climbing to 2500, intercept ADW VORTAC R-191 to PREZZ and hold.

ATIS	POTOMAC APP CON	ANDREWS TOWER	GND CON	CLNC DEL	CPDLC
133.675 251.05	128.0 335.5	118.4 349.0	121.8 275.8	127.55 285.475	

CATEGORY III ILS-SPECIAL AIRCREW & AIRCRAFT CERTIFICATION REQUIRED

† For aircraft not equipped with TACAN or suitable RNAV system with GPS: Fly hdg 190°, maintain 2000 expect RADAR vectors.



ELEV 280 | TDZE 274





CATEGORY	A	B	C	D	E
S-ILS 19R	CAT IIIa RVR 07				
S-ILS 19R	CAT IIIb RVR 06				
S-ILS 19R	CAT IIIc NA				

CAMP SPRINGS, MARYLAND — 38°49'N-76°52'W — JOINT BASE ANDREWS (KADW)

Amdt 4 05DEC19

ILS RWY 19R (CAT III)

NE-3, 31 DEC 2020 to 28 JAN 2021