

WAAS

CH **65621**

W04A

APP CRS

045°

Rwy Idg

5130

TDZE

51

Apt Elev

53

RNAV (GPS) RWY 4

DELAWARE COASTAL (GED)

▼

DME/DME RNP-0.3 NA. When local altimeter setting not received, use Salisbury altimeter setting and increase LPV DA to 353 feet, LNAV/VNAV DA to 555 feet, increase all MDA 60 feet.

▲

Increase LNAV/VNAV all Cats visibility to 1 ½ mile, LNAV Cats C/D visibility to 1 ¼ mile and increase Circling Cat C visibility to 2 miles and Cat D visibility to 2 ¼ miles. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -13°C (9°F) or above 54°C (130°F). Baro-VNAV and VDP NA when using Salisbury altimeter setting. For inoperative MALSS increase LNAV/VNAV all Cats and LNAV Cats C/D visibility ¼ mile. For inoperative MALSS increase LNAV/VNAV all Cats and LNAV Cats C/D visibility ¼ mile. For inoperative MALSS increase LNAV/VNAV all Cats and LNAV Cats C/D visibility ¼ mile. For inoperative MALSS increase LNAV/VNAV all Cats and LNAV Cats C/D visibility ¼ mile. Night Landing: Rwy 10, 28 NA.

MALS

MISSED APPROACH: Climb to 2000 direct HUVOX and hold.

ASOS 118.375	DOVER APP CON 132.425 257.875	UNICOM 123.0 (CTAF) 0
------------------------	---	---------------------------------

30 NM to ZARVI

2100

135°

315°

ZARVI

30 NM to ZARVI

2000

2100

135°

315°

ZARVI (NoPT)

1048

R-4006

260

205

RW04

(FAF) SABER

2000

045°

225°

4 NM

(IF/IAF) ZARVI

4 NM Holding Pattern

ZARVI

SABER

2000

HUVOX

2000

045°

225°

GP 3.00°

TCH 45

7 NM

4.7 NM

1.3 NM

*1.3 NM to RW04

*LNAV only.

RW04

5530 x 150

3109 x 75

28

045° to RW04

REIL Rwy 4, 22, 10, and 28

MIRL Rwy 4-22 and 10-28

CATEGORY	A	B	C	D
LPV DA	301-¾	250 (300-¾)		
LNAV/VNAV DA	503-1¼	452 (500-1¼)		
LNAV MDA	520-¾	469 (500-¾)	520-1⅛	469 (500-1⅛)
CIRCLING	560-1 507 (600-1)	580-1 527 (600-1)	720-1¾ 667 (700-1¾)	720-2 667 (700-2)

GEORGETOWN, DELAWARE

Amtd 3 04FEB16

38°41'N-75°22'W

DELAWARE COASTAL (GED)

RNAV (GPS) RWY 4