

ILS or LOC RWY 6
ERIE INTL/TOM RIDGE FIELD (ERI)

T Circling to Rwy 2, 20 NA at night. Circling NA SE of Rwy 6-24. Autopilot coupled approach NA below 1580. VDP NA with Ashtabula, OH altimeter setting. increase SHLS 6 all
A Cats visibility to RVR 6000, S-LOC 6 Cats C/D visibility to 1% SM. For inop MALSR, increase S-LOC 6 Cats C/D visibility to RVR 6000. When local altimeter setting not received, use Ashtabula, OH altimeter setting and increase DA to 1078 and all MDA 100 feet, increase ILS all Cats to RVR 3000 and increase S-LOC 6 Cats C/D visibility to RVR 5500 and Circling Cat D visibility to 2 1/4 SM.



MISSED APPROACH:
Climb to 1300 then
climbing left turn to
4000 on heading
330° and on
ERI VORTAC
R-030 direct
ERI VORTAC
and hold.

Use I-ERI DME when on the localizer course.

CATEGORY	A	B	C	D
S-ILS 6	982/24 250 (300-½)			
S-LOC 6	1140/24	408 (500-½)	1140/40	408 (500-¾)
C CIRCLING	1160-1 428 (500-1)	1200-1 468 (500-1)	1200-1½ 468 (500-1½)	1340-2 608 (700-2)

NE-4, 31 DEC 2020 to 28 JAN 2021

NE-4, 31 DEC 2020 to 28 JAN 2021