

LOC/DME I-HZL

**110.5**

Chan **42**

APP CRS

**284°**

Rwy Idg

**4898**

TDZE

**1603**

Apt Elev

**1603**

LOC RWY 28

HAZLETON RGNL (HZL)

RNAV 1-GPS required for procedure entry.  
RNAV 1-GPS required from MAP to ECEDI.

▼

NA

Rwy 28 helicopter visibility reduction below ¾ SM NA. Inop table does not apply to Cats A/B. For inop ALS, increase Cat C/D visibility to 1 ¾ SM.

MALS

MISSED APPROACH:

Climb to 4400 direct ECEDI and hold.

AWOS-3 <b>119.975</b>	WILKES-BARRE APP CON <b>126.3 256.7</b>	CLNC DEL <b>121.7</b>	UNICOM <b>123.0 (CTAF) 0</b>
--------------------------	--------------------------------------------	--------------------------	---------------------------------

Diagram illustrating the approach procedure for HAZLETON RGNL (HZL) LOC RWY 28. The diagram shows the approach path, including the localizer (110.5), various altitudes (1791, 1712, 1868, 2127, 2184, 2220, 2965), and the holding pattern at 6000/4200. The diagram also shows the Weiss and Wagdu intersection points and the final approach segment.

ELEV **1603**

**D**

TDZE **1603**

MISSED APCH FIX

ECEDI

104°

284°

5 NM

REIL Rwy 10

MRL Rwy 10-28

FAF to MAP 4.9 NM

Knots	60	90	120	150	180
Min:Sec	4:54	3:16	2:27	1:58	1:38

4400

ECEDI

WAGDU INT I-HZL **5.9**

I-HZL **2.9**

I-HZL **0.9**

3.00°

TCH 40

1.9

3 NM

7 NM

WEISS INT I-HZL **12.8**

One Minute Holding Pattern

104°

284°

6000

4200

CATEGORY	A	B	C	D
S-LOC 28	2280-1 677 (700-1)		2280-1¾ 677 (700-1¾)	
CIRCLING	2280-1 677 (700-1)	2400-1 797 (800-1)	2480-2½ 877 (900-2½)	2520-3 917 (1000-3)

HAZLETON, PENNSYLVANIA

Amtd 9 25APR19

40°59'N-76°00'W

HAZLETON RGNL (HZL)

LOC RWY 28