

WAAS
CH **45616**
W23A

APP CRS
233°

Rwy Idg
TDZE
Apt Elev
6215
931
947

RNAV (GPS) Y RWY 23

YEAGER (CRW)

⚠

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (4°F) or above 54°C (130°F). DME/DME RNP-0.3 NA.
For inoperative ALSF, increase LNAV/VNAV all Cats visibility to 2¼.
**RVR 1800 authorized with use of FD or AP or HUD to DA.

ALSF-1

ⓐ1

MISSED APPROACH: Climb to 1400 then climbing right turn to 3000 direct HVQ VOR/DME and hold.

ATIS 127.6	CHARLESTON APP CON 124.1 269.125	CHARLESTON TOWER 125.7 257.8	GND CON 121.8 348.6	CLNC DEL 118.55
----------------------	--	--	-------------------------------	---------------------------

ELEV **947**

D

TDZE **931**

1400

3000

HVQ

↑

↷

◻

*LNAV only.

1.7 NM to RW23

0.6 NM

2.2 NM

6.5 NM

1.7 NM

0.6 NM

2.2 NM

6.5 NM

CATEGORY

A

B

C

D

LPV

DA**

1131/24

200 (200-½)

LNAV/VNAV

DA

1601-1⅞

670 (700-1⅞)

LNAV

MDA

1500/24

569 (600-½)

1500-1⅓

569 (600-1⅓)

C CIRCLING

1600-1

653 (700-1)

1760-2½

813 (900-2½)

1760-2¾

813 (900-2¾)

CHARLESTON, WEST VIRGINIA

Amdt 1B 07DEC17

38°23'N-81°36'W

YEAGER (CRW)

RNAV (GPS) Y RWY 23