

WAAS CH <b>8651B</b> <b>W16B</b>	APP CRS <b>164°</b>	Rwy Idg TDZE <b>364</b> Apt Elev <b>374</b>	<b>8009</b>
--	------------------------	---	-------------

# RNAV (GPS) Y RWY 16R

MAHLON SWEET FIELD (EUG)


RNP APCH.

Simultaneous approach authorized. LNAV procedure NA during simultaneous operations. Use of FD or AP providing RNAV track guidance required during simultaneous operations. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -10°C or above 54°C. For inop ALS, increase LNAV/VNAV all Cats visibility to RVR 4500, increase LNAV Cat C/D visibility to RVR 5500.

ALSF-2

MISSED APPROACH: Climb to 5000 direct TIPIE and on track 229° to VAUGN and hold, continue climb-in-hold to 5000.

ATIS <b>125.225</b>	CASCADE APP CON ★ <b>119.6 348.7</b>	EUGENE TOWER ★ <b>118.9</b> (CTAF) <b>371.9</b> (Rwy 16R/34L) <b>124.15 371.9</b> (Rwy 16L/34R)	GND CON <b>121.7 269.5</b>	CLNC DEL <b>121.7 269.5</b>	UNICOM <b>122.95</b>
------------------------	---	---	-------------------------------	--------------------------------	-------------------------



	HOCUM	WATAL	5000	TIPIE	tr 229°	VAUGN
	4000	2000				
	GP 3.00° TCH 51		WENIT 3 NM to RWY 16R	*1 NM to RWY 16R	*LNAV only	
CATEGORY	A	B	C	D		
LPV DA		564/18	200 (200-½)			
LNAV/VNAV DA		628/24	264 (300-½)			
LNAV MDA	720/24	356 (400-½)	720/30	356 (400-¾)		
CIRCLING	820-1 446 (500-1)	840-1 466 (500-1)	1000-1¾ 626 (700-1¾)	1140-2½ 766 (800-2½)		

