

APP CRS	Rwy Idg	9007
020°	TDZE	2966
	Apt Elev	2977

RNAV (RNP) Y RWY 2
GLACIER PARK INTL (GPI)

RF and GPS required. Missed approach requires RNP less than 1.0.
For uncompensated Baro-VNAV systems, procedure NA below -21°C (-5°F) or above 43°C (109°F). For inoperative MALSR increase RNP 0.10* visibility to 1¼ and RNP 0.30 visibility to 2.
*Missed approach requires minimum climb of 220 feet per NM to 6100.

MALSR
A5

MISSED APPROACH: Climb to 10000 via left turn to JOGAD, and via left turn to TONUY, and via 121° track to WILTO and via 129° track to ANGL and hold.

ATIS 132.625	SALT LAKE CENTER 133.4 285.4	GLACIER TOWER ★ 124.55 (CTAF) 0	GND CON 121.6	UNICOM 122.95
-----------------	---------------------------------	------------------------------------	------------------	------------------



ELEV 2977 **D** TDZE 2966

REIL Rwy 20 0
MIRL Rwy 12-30 0
HIRL Rwy 2-20 0

Procedure Turn NA

GP 3.00°
TCH 51

3 NM 3.2 NM 7.1 NM 6.7 NM

CATEGORY	A	B	C	D
RNP 0.10 DA*	NA	3340-¾	374 (400-¾)	
RNP 0.30 DA	NA	3522-1½	556 (600-1½)	

10000 JOGAD

ROYOG

BINGQ

RWY 2

AUTHORIZATION REQUIRED

NW-1, 31 DEC 2020 to 28 JAN 2021

NW-1, 31 DEC 2020 to 28 JAN 2021