

LOC I-EVG 111.7	APCH CRS 126°	Rwy Idg 10,000 TDZE 1241 Arprt Elev 1291	AL-299 [USAF]	TINKER AFB (KTIK)
---------------------------	-------------------------	---	---------------	-------------------

*** When ALS inop, increase CAT AB RVR to 50 and vis to 1 mile, CAT C RVR to 60 and vis to 1¼ miles, CAT D vis to 1½ miles, CAT E vis to 1¾ miles.**

ATIS ★ 270.1	OKE CITY APP CON 124.2 336.4	TINKER TOWER 124.45 251.05	GND CON 121.8 275.8	CLNC DEL 119.7 335.8	ASR
------------------------	--	--------------------------------------	-------------------------------	--------------------------------	-----

**** CAT E Circling not authorized in sector S of Rwy 13-31 and W of Rwy 18-36.**

CAUTION: VFR Flyway from FAF to MAP, SFC to 3000 MSL.

Max holding 230 KIAS
Max holding alt 6000

(IAF) ZEMGU

WURIS

LOCALIZER 111.7 I-EVG

WILL ROGERS 114.1 IRW Chan 88

RADAR REQUIRED

Max holding 230 KIAS
Max holding alt 6100

WEVAV IRW 25

EMERG SAFE ALT 100 NM 4700

ZEMGU IRW I-EVG R-354 LOC	WURIS IRW R-028	2500	IRW R-075	3000 WEVAV R-075
---------------------------	-----------------	------	-----------	------------------

CATEGORY	A	B	C	D	E
S-13 *	1740/40	499 (500-¾)	1740/50 499 (500-1)	1740/60 499 (500-1¼)	1740-1½ 499 (500-1½)
CIRCLING **	1880-1	589 (600-1)	1880-1½ 589 (600-1½)	1980-2¼ 689 (700-2¼)	2040-2¾ 749 (800-2¾)

126° 6.0 NM from FAF

10,000 x 200 0-5% UP

11,100 x 200 0-3% UP

HIRL Rwy 18-36, 13-31

FAF to MAP 6 NM

Knots	60	90	120	150	180
Min:Sec	6:00	4:00	3:00	2:24	2:00

126° 6.0 NM from FAF

10,000 x 200 0-5% UP

11,100 x 200 0-3% UP

HIRL Rwy 18-36, 13-31

FAF to MAP 6 NM

Knots	60	90	120	150	180
Min:Sec	6:00	4:00	3:00	2:24	2:00