

WAAS CH 77825 W04A	APP CRS 044°	Rwy Idg TDZE Apt Elev	6001 279 279
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 4

WALNUT RIDGE RGNL (ARG)

⚠

Baro-VNAV NA when using Jonesboro altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 42°C (107°F). DME/DME RNP-0.3 NA. VDP NA with Jonesboro altimeter setting. When local altimeter setting not received, use Jonesboro altimeter setting and increase all DA 54 feet and all MDA 60 feet; increase LPV and LNAV/VNAV all Cats visibility ¼ mile and LNAV Cat C and D visibility ½ mile.

MALSF

MISSED APPROACH:

Climb to 2700 direct ESEGE and hold.

AWOS-3PT 135.925	MEMPHIS CENTER 120.075 289.4	UNICOM 122.8 (CTAF) 0
----------------------------	--	---------------------------------

30 NM to XIHAM
134°
314°
3100
XIHAM
314°
30 NM to XIHAM (NoPT)
6 NM to XIHAM
2700
XIHAM
044°
224°
4 NM
(IF/IAF) XIHAM
1900
044° (6.8)
(FAF) ZUPTA
TILVE 1.5 NM to RW04
395
359 ± 13
RW04
Δ 688

4 NM Holding Pattern		XIHAM		ZUPTA		TILVE 1.5 NM to RW04		2700	ESEGE				
2700		←224°		044°→		044°		*LNAV only.					
GP 3.00°		TCH 45		1900		*800		RW04					
		6.8 NM		3.5 NM		0.6		0.9					
CATEGORY	A	B	C	D									
LPV DA	529-¾		250 (300-¾)										
LNAV/VNAV DA	529-¾		250 (300-¾)										
LNAV MDA	620-1		341 (400-1)										
CIRCLING	760-1	481 (500-1)	760-1½	840-2									
			481 (500-1½)	561 (600-2)									

Δ 1430
ELEV 279 TDZE 279
5002 X 150
81
5001 X 150
338
36
6001 X 150
044° to RW04
REIL Rwy 18
MIRL Rwy 4-22, 18-36

WALNUT RIDGE, ARKANSAS

Orig-A 29MAY14

36°07'N-90°56' W

WALNUT RIDGE RGNL (ARG)

RNAV (GPS) RWY 4