

LOC/DME I-PNC
111.9
Chan **56**

APP CRS
175°

Rwy Idg
TDZE
Apt Elev
7201
1004
1008

ILS or LOC/DME RWY 17

PONCA CITY RGNL (PNC)

When local altimeter setting not received, use Winfield-Arkansas City altimeter setting and increase S-ILS 17 DA 82 feet and all MDA 100 feet; increase S-LOC Cat C and D and Circling Cat C visibility ¼ mile. For inop MALS, when using Winfield-Arkansas City altimeter setting, increase S-ILS 17 visibility to 1 mile all Cats. VDP NA when using Winfield-Arkansas City altimeter setting.

MALS
A5

MISSED APPROACH:
Climb to 2500 then climbing right turn to 2700 direct PER VORTAC and hold.

ASOS 134.075	KANSAS CITY CENTER 127.8 319.1	UNICOM 123.0 (CTAF) 0
------------------------	--	---------------------------------

One Minute Holding Pattern

TOMHO I-PNC 12.6

OKTAE I-PNC 6.5

2500

2700

PER

2700

355°

175°

2700

175°

GS 3.00°

TCH 48

6.1 NM

3.6 NM

1.5 NM

CATEGORY	A	B	C	D
S-ILS 17	1204-½ 200 (200-½)			
S-LOC 17	1520-½ 516 (600-½)		1520-1 516 (600-1)	1520-1¼ 516 (600-1¼)
CIRCLING	1520-1 512 (600-1)		1560-1½ 552 (600-1½)	1560-2 552 (600-2)

ELEV 1008

TDZE 1004

175° 5.1 NM from FAF

41

A5

1050

7201 X 130

35

HIRL Rwy 17-35 0

PONCA CITY, OKLAHOMA

Amdt 3 25SEP08

36°44'N-97°06'W

PONCA CITY RGNL (PNC)

ILS or LOC/DME RWY 17