

LOC/DME I-ROG	APP CRS	Rwy Idg	6011
111.5	195°	TDZE	1354
Chan 52		Apt Elev	1359

ILS or LOC RWY 20

ROGERS EXECUTIVE-CARTER FIELD (ROG)

DME Required.

Autopilot coupled approach NA below 1632.

MALSR

MISSED APPROACH: Climb to 2100, then climbing left turn to 4000 on heading 110° and RZC VORTAC R-048 to TEEUP INT/RZC 12.6 DME and hold.

AWOS-3PT	RAZORBACK APP CON★	ROGERS TOWER★	GND CON	CLNC DEL
134.375	126.6 305.2	119.375 (CTAF) 0	118.0	121.75

2100

4000

RZC R-048

TEEUP

↑

hdg 110°

Use I-ROG DME when on LOC course.

*LOC only.

WARPA I-ROG 3.9

FIGBO I-ROG 6.5

NASIC I-ROG 13.2

I-ROG 1.2

I-ROG 2.2

*2240

3100

3200

195°

3100

GS 3.00° TCH 55

1.1 NM

1.6 NM

2.7 NM

6.7 NM

CATEGORY	A	B	C	D
S-ILS 20	1554-½ 200 (200-½)			
S-LOC 20	1740-½ 386 (400-½)		1740-⅝ 386 (400-⅝)	
CIRCLING	1820-1 461 (500-1)		2020-1¾ 661 (700-1¾)	

ELEV 1359

TDZE 1354

195° 5.4 NM from FAF

0.3% UP

6011 X 100

TWR

REIL Rwy 2 0

HIRL Rwy 2-20 0

FAF to MAP 5.4 NM

Knots	60	90	120	150	180
Min:Sec	5:24	3:36	2:42	2:10	1:48

ROGERS, ARKANSAS

Amtd 4 17AUG17

36°22'N-94°06'W

ROGERS EXECUTIVE-CARTER FIELD (ROG)

ILS or LOC RWY 20