

RADAR INSTRUMENT APPROACH MINIMUMS

FORT SMITH, AR
FORT SMITH RGNL (FSM)
RADAR-1 120.9 343.75

Amdt 8D, 20JUN19 (19171) (FAA)

ELEV **469**

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/ MDA-VIS</u>	<u>HAT/ HAA</u>	<u>CEIL-VIS</u>	<u>CAT</u>	<u>DA/ MDA-VIS</u>	<u>HAT/ HAA</u>	<u>CEIL-VIS</u>
ASR	25		AB	1040/24	594	(600-½)	C	1040/50	594	(600-1)
			D	1040/60	594	(600-1¼)	E	1040-1½	594	(600-1½)
	1		AB	1140-1	692	(700-1)	C	1140-2	692	(700-2)
			D	1140-2¼	692	(700-2¼)	E	1140-2½	692	(700-2½)
	7		AB	1200-½	731	(800-½)	C	1200-1½	731	(800-1½)
			D	1200-1¾	731	(800-1¾)	E	1200-2	731	(800-2)
CIRCLING	ALL RWY	AB	1200-1	731	(800-1)	C	1200-2	731	(800-2)	
		D	1200-2¼	731	(800-2¼)	E	1200-2½	731	(800-2½)	

When control tower closed ASR not authorized.
Rwy 1 helicopter visibility reduction below ¾ SM not authorized.
Rwy 7 helicopter visibility reduction below ¾ SM not authorized.
Circling CAT E NA when R-2401B active.
Circling NA northwest of Rwy 7 and 19 for CAT E.
For inoperative MALSR, increase S-7 CAT E visibility to 2½ miles, and S-25 CAT E visibility to 2 miles.

HENRY POST AAF (KFSI), OK (Fort Sill) (Amdt 13, 19171 USA)
RADAR - (E) 120.55 322.4 NA

ELEV **1188**

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/ MDA-VIS</u>	<u>HAT/ HATH/ HAA</u>	<u>CEIL-VIS</u>
ASR	36 ²		AB	1600/40	413	(500-¾)
			CDE	1600/50	413	(500-1)
AB	1880-1		692	(700-1)		
CDE	1880-2		692	(700-2)		
CIR ¹	18-36		AB	1880-1	692	(700-1)
			C	1880-2	692	(700-2)
			D	1920-2¼	732	(800-2¼)
			E	1940-2¾	752	(800-2¾)

When local altimeter setting not received, use Lawton-Ft Sill Rgnl altimeter setting.
¹Circling NA for CAT E W of Rwy 18-36.
²When ALS inop, increase CAT CDE RVR to 60.

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR INSTRUMENT APPROACH MINIMUMS

LAWTON, OK
RADAR-1 - 120.55 322.4

Amdt 4A, 10JAN00 (00010) (FAA)

ELEV 1110

LAWTON-FORT SILL RGNL (LAW)

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>
ASR	35		ABC	1560-¾	471	(500-¾)	D	1560-1	471	(500-1)
CIRCLING	ALL RWY		AB D	1600-1 1680-2	490 570	(500-1) (600-2)	C	1620-1½	510	(600-1½)

LAWTON, OK
RADAR-2 - 120.55 322.4

Amdt 1B, 08AUG02 (02220) (FAA)

ELEV 1110

LAWTON-FORT SILL RGNL (LAW)

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VS</u>
ASR	17		AB	1620-1	510	(600-1)	CD	1620-1½	510	(600-1½)
CIRCLING	ALL RWY		AB D	1620-1 1680-2	510 570	(600-1) (600-2)	C	1620-1½	510	(600-1½)

OKLAHOMA CITY, OK
WILEY POST (PWA)
RADAR-1 124.6 266.8

Amdt 2A, 07APR11 (11153) (FAA)

ELEV 1299


	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>
ASR	35R		AB D	1840-1 1840-1¾	541 541	(600-1) (600-1¼)	C	1840-1½	541	(600-1½)
CIRCLING	ALL RWY		AB D	1840-1 1880-2	541 581	(600-1) (600-2)	C	1840-1½	541	(600-1½)

31 DEC 2020 to 28 JAN 2021

31 DEC 2020 to 28 JAN 2021

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR INSTRUMENT APPROACH MINIMUMS

OKLAHOMA CITY, OK
WILL ROGERS WORLD (OKC)
RADAR-1 124.6 266.8 

Amdt 21A, 13OCT16 (20030) (FAA) ELEV 1296

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/ MDA-VIS</u>	<u>HAT/ HAA</u>	<u>CEIL-VIS</u>
ASR	17L		ABCDE	1680/40	393	(400-¾)
	35R		ABCDE	1680/40	386	(400-¾)
	17R		ABCDE	1680/40	398	(400-¾)
	35L		ABCDE	1680/40	404	(400-¾)
CIRCLING	ALL RWY		A	1740-1¼	444	(500-1¼)
			B	1760-1¼	464	(500-1¼)
			C	1960-1¼	664	(700-1¼)
			D	2000-2¼	704	(800-2¼)
			E	2240-3	944	(1000-3)

For inoperative MALSR, increase S-17L, S-17R, and S-35L CAT E visibility to 1¼.
For inoperative ALSF, increase S-35R CAT E visibility to 1¼.

31 DEC 2020 to 28 JAN 2021

31 DEC 2020 to 28 JAN 2021

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR INSTRUMENT APPROACH MINIMUMS

TINKER AFB (KTIK), (Oklahoma City) OK (20086 USAF)
RADAR - Ctc OKLAHOMA CITY APP CON (E) 118.95 323.1 

ELEV 1291

RADAR - Cte OKLAHOMA CITY APP CON (E) 118.95 323.1					HAT/ HATH/
	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/ MDA-VIS</u>	<u>CEIL-VIS</u>
ASR	36 ¹		A	1940/24	649 (700-½)
			B	1940/40	649 (700-¾)
			C	1940/60	649 (700-1¼)
			D	1940-1½	649 (700-1½)
			E	1940-1¾	649 (700-1¾)
	18 ²		A	2000/40	733 (800-¾)
			B	2000/50	733 (800-1)
			C	2000-1¾	733 (800-1¾)
			D	2000-2	733 (800-2)
			E	2000-2¼	733 (800-2¼)
CIR ³	36		A	1940-1	649 (700-1)
			B	1940-1¼	649 (700-1¼)
			C	1940-1¾	649 (700-1¾)
			D	1980-2¼	689 (700-2¼)
			E	2040-2¾	749 (800-2¾)
	18		A	2000-1	709 (800-1)
			B	2000-1¼	709 (800-1¼)
			C	2000-2	709 (800-2)
			D	2000-2¼	709 (800-2¼)
			E	2040-2¾	749 (800-2¾)

¹When ALS inop, increase CAT A RVR to 50 and vis to 1 mile, CAT B RVR to 60 and vis to 1¼ miles, CAT C vis to 1¾ miles, CAT D vis to 2 miles, CAT E vis to 2¼ miles.

²When ALS inop, increase CAT A RVR to 50 and vis to 1 mile, CAT B RVR to 60 and vis to 1¼ miles, CAT C vis to 2 miles, CAT D vis to 2¼ miles, CAT E vis to 2½ miles.


³CAT E circling not authorized in sector S of Rwy 13-31 and W of Rwy 18-36.

31 DEC 2020 to 28 JAN 2021

31 DEC 2020 to 28 JAN 2021

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR INSTRUMENT APPROACH MINIMUMS

TULSA, OK
TULSA INTL (TUL)
RADAR-1 124.0 338.3 

Amdt 18, 13JAN11 (15008) (FAA)

ELEV 677

ASR	RWY	GP/TCH/RPI	CAT	DA/ MDA-VIS	HAT/ HAA	CEIL-VIS	CAT	DA/ MDA-VIS	HAT/ HAA	CEIL-VIS
	26		AB	1060-1	409	(400-1)	CD	1060-1¼	409	(400-1¼)
			E	1060-1½	409	(400-1½)				
	18L		AB	1080/24	439	(500-½)	C	1080/40	439	(500-¾)
			DE	1080/50	439	(500-1)				
	36R		AB	1140/24	490	(500-½)	C	1140/40	490	(500-¾)
			D	1140/50	490	(500-1)				
	18R		AB	1080-1	413	(500-1)	CD	1080-1¼	413	(500-1¼)
			E	NA						
	8		AB	1120-1	449	(500-1)	C	1120-1¼	449	(500-1¼)
			DE	1120-1½	449	(500-1½)				
	36L		AB	1180-1	503	(600-1)	CD	1180-1½	503	(600-1½)
			E	NA						
CIRCLING	ALL RWY		AB	1180-1	503	(600-1)	C	1180-1½	503	(600-1½)
			D	1300-2	623	(700-2)				

Circling NA for CAT E South of runway 8-26.

31 DEC 2020 to 28 JAN 2021

31 DEC 2020 to 28 JAN 2021