

RNAV (GPS) RWY 35L  
DALLAS-FORT WORTH INTL (DFW)

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -4°C (25°F) or above 54°C (130°F). Simultaneous approach authorized with Rwy 36L/R and Rwy 35R. DME/DME RNP-0.3 NA. LNAV procedure NA during simultaneous operations. Use of FD or AP providing RNAV track guidance required during simultaneous operations.



**MISSED APPROACH:**  
Climb to 3000 direct  
BBAKR and on track  
357° to BOSSI and  
hold.

D-ATIS	REGIONAL APP CON 127.075	DFW TOWER		GND CON		CLNC DEL 128.25	CPDLC
ARR 123.775		126.55	127.5 EAST	121.65	121.8 EAST		
DEP 135.925		124.15	134.9 WEST	121.85	WEST		

**RADAR REQUIRED**

357° (12) BBAKR

804 1016

RW35L

(FAF) BEGGO

2300 356° (2.4) DALLN

3000 356° (6.3)

CORMN 5000 356° (3.2)

(IF) TANDU 1897

**MISSED APCH FIX**

4 NM 356° 176° BOSSI

**MSA RW35L 25 NM**

3600

ELEV	607	<b>D</b>	TDZE	564
------	-----	----------	------	-----

MSA RW35L 25 NM

3600

DALLAS-FORT WORTH INTL (DFW)  
RNAV (GPS) RWY 35L