

WAAS CH 57999 W35A	APP CRS 353°	Rwy Idg 6002 TDZE 697 Apt Elev 700
--	------------------------	---

RNAV (GPS) RWY 35L

FORT WORTH SPINKS (FWS)

⚠ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 39°C (102°F). Circling NA west of Rwy 17R-35L. DME/DME RNP-0.3 NA. Baro-VNAV and VDP NA when using Fort Worth Meacham altimeter setting. When local altimeter setting not received, use Fort Worth Meacham altimeter setting and increase all DA 37 feet and all MDA 40 feet, increase LNAV/VNAV all Cats visibility ⅓ mile. For inop MALSR increase LNAV/VNAV all Cats visibility to 1⅓ mile and increase LNAV Cats C/D visibility to 1⅓ mile. For inop MALSR when using Fort Worth Meacham altimeter setting, increase LNAV/VNAV all Cats visibility to 1¼ mile and LNAV Cats C/D visibility to 1⅓ mile.

MALSR

MISSED APPROACH:
Climb to 1400 then climbing left turn to 3100 direct SLUGG and hold.

ATIS 120.025	REGIONAL APP CON 135.975 379.9	SPINKS TOWER ★ 124.625 (CTAF) 0	GND CON 119.475	UNICOM 122.7
------------------------	--	--	---------------------------	------------------------

