

APP CRS
295°

Rwy Idg
TDZE
777

Apt Elev
790

RNAV (GPS) RWY 29

GEORGETOWN MUNI (GTU)

RNP APCH.

▼ Rwy 29 helicopter visibility reduction below ¾ SM NA. VDP NA when using Skylark Field altimeter setting. When local altimeter setting not received, use Skylark Field altimeter setting and increase all MDA 80 feet increase LNAV and Circling Cat C/D visibility ¼ SM.

MISSED APPROACH: Climbing right turn to 3000 direct DARTE and hold.

ATIS
118.6

AUSTIN APP CON
119.0 370.85

GEORGETOWN TOWER ★
120.225 (CTAF) 0

GND CON
119.125

CLNC DEL
119.125

CLNC DEL
121.1
(when twr closed)

UNICOM
123.0

ELEV 790

TDZE 777

81

5004 X 100

TWR

0.8% UP

0.7% UP

36

295° to RW29

REIL Rwy 18 and 36

MIRL Rwy 11-29 and 18-36

3000

DARTE

HEGUR 3 NM to RW29

IWKOK

KOJCY

3000

1.2 NM to RW29

1.8

2 NM

6.2 NM

1760

2400

295°

CATEGORY	A	B	C	D
LNAV MDA	1220-1	443 (500-1)	1220-1¾	443 (500-1¾)
CIRCLING	1240-1 450 (500-1)	1340-1 550 (600-1)	1360-1½ 570 (600-1½)	1640-2¾ 850 (900-2¾)

GEORGETOWN, TEXAS

Amdt 1A 16JUL20

30°41'N-97°41'W

GEORGETOWN MUNI (GTU)

RNAV (GPS) RWY 29