

WAAS CH <b>63109</b> <b>W36A</b>	APP CRS <b>002°</b>	Rwy Idg <b>8497</b> TDZE <b>15</b> Apt Elev <b>23</b>
--	------------------------	---

RNAV (GPS) RWY 36  
STENNIS INTL (HSA)

⚠ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). Circling NA for Cat E West of Rwy 18-36. DME/DME RNP-0.3 NA. Helicopter visibility reduction below ¾ SM NA. Baro-VNAV and VDP NA when using Gulfport altimeter setting. When local altimeter setting not received, use Gulfport altimeter setting and increase LPV DA to 332 feet and LNAV/VNAV DA to 344 feet and all MDA 60 feet; increase LPV and LNAV/VNAV all Cats visibility ½ mile and LNAV Cats C/D/E and Circling Cats D/E visibility ¼ mile.

MISSED APPROACH: Climb to 2000  
direct STENN and hold.

AWOS-3PT <b>118.375</b>	GULFPORT APP CON ★ <b>124.6 354.1</b>	STENNIS TOWER ★ <b>127.15</b> (CTAF) <b>0</b>	GND CON <b>121.725</b>	UNICOM <b>122.95</b>
----------------------------	--	--	---------------------------	-------------------------

