

WAAS CH 45818 W18A	APP CRS 180°	Rwy Idg 5001 TDZE 44 Apt Elev 47
--	------------------------	---

RNAV (GPS) RWY 18

HAMMOND NORTHSORE RGNL (HDC)

- V** Baro-VNAV NA when using Louis Armstrong New Orleans Intl altimeter setting.
A For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 49°C (120°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Louis Armstrong New Orleans Intl altimeter setting and increase all DA 89 feet and all MDA 100 feet. Increase LNAV/VNAV all Cats, LNAV Cats C and D, and Circling Cat D visibility 1/4 mile. For inoperative MALSR increase LNAV Cat D visibility to 1/4 mile. For inoperative MALSR when using Louis Armstrong New Orleans Intl altimeter setting increase LPV all Cats visibility to 1 mile. VDP NA with Louis Armstrong New Orleans Intl altimeter setting.

MALSR



MISSED APPROACH:
Climb to 2200 direct
LYRON and hold.

ATIS 118.325	NEW ORLEANS APP CON 119.3 350.35	HAMMOND TOWER ★ 120.575 (CTAF) 0	GND CON 119.85	CLNC DEL 119.3 (When twr closed)
------------------------	--	---	--------------------------	---

