WAAS	APP CRS	Rwy Idg	8001
CH 48941	347°	TDZE	2131
W35A		Apt Elev	2164

RNAV (GPS) RWY 35

ASHEVILLE RGNL (AVL)

RNP APCH.

Circling NA west of Rwy 17-35. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -13°C or above 54°C. For inop ALS, increase LNAV Cat C/D visibility to 1⅜ SM.

MALSR

MISSED APPROACH: Climb to 6800 direct ONZIQ and hold, continue climb-in-hold to 6800.

ATIS	ASHEVILLE APP CON★	ASHEVILLE TOWER★	GND CON	UNICOM
120.2	124.65 269.575	121.1 (CTAF) L 257.8	121.9	122.95



ELEV 2164 D TDZE 2131



HIRL Rwys 17-35 L
REIL Rwys 17 and 35



CATEGORY	A	B	C	D
LPV DA	2334/24 203 (200-½)			
LNAV/VNAV DA	2567/40 436 (500-¾)			
LNAV MDA	2660/24 529 (500-½)		2660/55 529 (500-1)	
C CIRCLING	2800-1 636 (700-1)	2880-1 716 (800-1)	3460-3 1296 (1300-3)	3720-3 1556 (1600-3)

SE-2, 31 DEC 2020 to 28 JAN 2021
SE-2, 31 DEC 2020 to 28 JAN 2021