

WAAS

CH **87011**

**W20A**

APP CRS

**197°**

Rwy Idg

**6505**

TDZE

**25**

Apt Elev

**26**

**RNAV (GPS) RWY 20**

PITT-GREENVILLE (PGV)

▼

▲

Night landing: Rwy 8 NA. Baro-VNAV NA when using Washington altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Washington altimeter setting: increase LPV DA to 271 feet and LNAV/VNAV DA to 344 feet and all MDA 60 feet; increase LNAV/VNAV all Cats and LNAV Cats C/D visibility ½ mile and increase Circling Cats C/D visibility ¼ mile. For inop MALS, increase LNAV/VNAV all Cats visibility to ¾ mile and LNAV Cats C/D visibility to 1 mile. For inop MALS when using Washington altimeter setting, increase LNAV/VNAV all Cats visibility to 1 mile.

MALS

MISSED APPROACH:  
Climb to 3100 direct BOWBO and hold, continue climb-in-hold to 3100.

AWOS-3 <b>128.425</b>	WASHINGTON CENTER <b>123.85 279.65</b>	CLNC DEL <b>122.35</b>	UNICOM <b>122.8 (CTAF)</b>
--------------------------	---	---------------------------	-------------------------------

NoPT for arrivals at KENIR on V290 southeast bound.

ELEV 26

**D**

TDZE 25

197° to RW20

02

7175 X 150

4997 X 150

26

2

HIRL Rwy 2-20

MIRL Rwy 8-26

REIL Rws 2, 8, and 26

3100		BOWBO		TROTH 1.5 NM to RW20		EVAXY 1400		KENIR 4 NM Holding Pattern					
*LNAV only		RW20		*540		1400		GP 3.00° TCH 50					
1.5 NM		2.7 NM		9.6 NM									
CATEGORY	A	B	C	D									
LPV DA	230-½		205 (300-½)										
LNAV/VNAV DA	303-½		278 (300-½)										
LNAV MDA	400-½		375 (400-½)		400-⅝		375 (400-⅝)						
CIRCLING	600-1		620-1		680-1¾		800-2½						
	574 (600-1)		594 (600-1)		654 (700-1¾)		774 (800-2½)						

GREENVILLE, NORTH CAROLINA

Amdt 3 04FEB16

35°38'N-77°23'W

PITT-GREENVILLE (PGV)

**RNAV (GPS) RWY 20**