


WAAS CH 42703 W08A	APP CRS 092°	Rwy Idg 8600 TDZE 9 Apt Elev 9
--	------------------------	---

RNAV (GPS) RWY 8L

MIAMI INTL (MIA)

RNP APCH.	▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below 5°C (41°F) or above 54°C (130°F). Simultaneous approach authorized with Rwy 9. Rwy 8L helicopter visibility reduction below ¾ SM NA. LNAV procedure NA during simultaneous operations. Use of FD or AP providing RNAV track guidance required during simultaneous operations.	MISSED APPROACH: Climb to 800 then climbing left turn to 3000 direct BRBRA and hold.
-----------	---	--

D-ATIS ARR 119.15 DEP 133.675	MIAMI APP CON 124.85 322.3	MIAMI TOWER 118.3 256.9	GND CON 121.8 (8L/8R/12/26L/26R) 127.5 (9/27/30)	348.6	CLNC DEL 135.35	CPDLC
---	--------------------------------------	-----------------------------------	--	--------------	---------------------------	-------



CATEGORY	A	B	C	D
LPV DA	279-1		270 (300-1)	
LNAV/VNAV DA	513-1½		504 (600-1½)	
LNAV MDA	600-1	591 (600-1)	600-1¾	591 (600-1¾)

