TAMPA, FLORIDA

ILS or LOC RWY 23

LOC I-GBZ	APCH CRS	Rwy ldg 11,421 TDZE 14 Arpt Elev 14
111.7	229°	

AL-418 [USAF]

MACDILL AFB (KMCF)

RADAR or DME required.

* When ALS inop, increase RVR to 40, vis to ¾ mile.
** When ALS inop, increase CAT AB RVR to 55, vis to 1 mile; CAT CDE vis to 1¼ miles.

ALSF-1

† MISSED APPROACH: Climb to 1600 via MCF R-223 to MILNE and hold.

ATIS	TAMPA APP CON	MACDILL TOWER	GND CON
133.825 270.1	124.95 354.0	120.175 294.7	118.575 275.8

*** Circling not authorized NW of Rwy 5-23.

† RNAV or ATC RADAR required for missed approach.

WARNING:
Use extreme caution
PETER O. KNIGHT arpt
4 NM NE of MACDILL AFB

Expect RADAR vectors around St. Petersburg landmass for noise abatement, unless otherwise requested by pilot.

MCF 16 055° 265K 235° R-055
049° 250°
(IAF) OZONA MCF 11
(CFDLL)
HUBOT MCF 7
MOBUE MCF 5
RADAR
229°
PETER O KNIGHT
475 640 625 626 244 517 649 649 217 500 410 1666
MACDILL Chan 47 MCF
LOCALIZER 111.7
I-GBZ
LOC offset 2.65°
R-223
MILNE MCF 15
043° 265K 223°
MCF 19
MSA MCF 25 NM
2700

CAUTION:
LOC course offset 2.68° from the extended rwy centerline and intersects the rwy centerline 1346' after the DA.

EMERG SAFE ALT 100 NM 3000

1600 MCF R-223
MILNE MCF 15
†† LOC only
MOBUE 5 RADAR 1600
HUBOT (CFDLL) 7
OZONA R-053 11
229° 250°
1700 1700 1600
TACAN
FANED .7
†† 1.3
GS 3.00°
TCH 54
4 4.3 NM

ELEV 14 TDZE 14

229° 4.8 NM from FAF

70 TWR 97 11,421 x 151 161 offset LOC

HIRL Rwy 5-23

CATEGORY	A	B	C	D	E
S-ILS 23 *	264/24 250 (300-½)				
S-LOC 23 **	440/24 426 (500-½)		440/40 426 (500-¾)		
CIRCLING ***	500-1 486 (500-1)	540-1 526 (600-1)	540-1½ 526 (600-1½)	580-2 566 (600-2)	1020-3 1006(1100-3)

LOC FAF to MAP 4.3 NM					
Knots	60	90	120	150	180
Min:Sec	4:18	2:52	2:09	1:43	1:26

SE-3, 31 DEC 2020 to 28 JAN 2021

SE-3, 31 DEC 2020 to 28 JAN 2021