

ATLANTA, GEORGIA

AL-26 (FAA)

ILS PRM RWY 26R (SA CAT I & II) (SIMULTANEOUS CLOSE PARALLEL)

HARTSFIELD-JACKSON ATLANTA INTL (ATL)

LOC/DME I-GXZ 110.1 Chan 38	APP CRS 275°	Rwy ldg 8500 TDZE 990 Apt Elev 1026
-------------------------------------------------	------------------------	-------------------------------------------------------------------------




Simultaneous close parallel approach authorized with ILS PRM and RNAV PRM Rwy 27R or 27L or 28, or Rwy 27R and 28, or Rwy 27L and 28. Procedure not authorized when glideslope not available. Dual VHF comm required. See additional requirements on AAPP. SA CAT I: Requires specific OPSPEC, MSPEC, or LOA approval and use of HUD to DH. SA CAT II: Reduced lighting: Requires specific OPSPEC, MSPEC, or LOA approval and use of autoland or HUD to touchdown.

MALSR



MISSED APPROACH: Climb to 1400 then climbing right turn to 3500 on ATL VORTAC R-005 to TROYS INT/ATL 15 DME and hold.

D-ATIS ARR 119.65 DEP 125.55	ATLANTA APP CON 127.9 379.9	ATLANTA TOWER 8L-26R 8R-26L 9L-27R 9R-27L 10-28 RWYS 119.1 125.325 123.85 119.3 119.5 254.4 PRM 126.9	ALL (8L-26R, 8R-26L) (9L-27R, 9R-27L) 10-28 RWYS 121.9 121.75 121.65 254.4	GND CON 121.9 121.75 121.65 254.4	ALL RWYS
--------------------------------------------------	------------------------------------------	------------------------------------------------------------------------------------------------------------------------------	-----------------------------------------------------------------------------------------	---------------------------------------------	-------------



CATEGORY	A	B	C	D
S-ILS 26R	SA CAT I	RA 170/14	150	DA 1140
S-ILS 26R	SA CAT II	RA 110/12	100	DA 1090

SA CATEGORY I & II ILS - SPECIAL AIRCREW & AIRCRAFT CERTIFICATION REQUIRED

ATLANTA, GEORGIA

33°38'N-84°26'W

HARTSFIELD-JACKSON ATLANTA INTL (ATL)

Amdt 3 18SEP14

ILS PRM RWY 26R (SA CAT I & II) (SIMULTANEOUS CLOSE PARALLEL)