

WAAS CH 70304 W32A	APP CRS 320°	Rwy Idg TDZE Apt Elev	9618 25 26
--	------------------------	-----------------------------	---------------------------------------

RNAV (GPS) RWY 32

MOBILE DOWNTOWN (BFM)

⚠

DME/DME RNP-0.3 NA. When local altimeter setting not received, use Mobile Rgnl altimeter setting and increase all DA 50 feet and MDA 60 feet and increase LNAV Cat C/D visibility to RVR 5500, and increase Circling Cat C visibility ¼ mile. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below 13°C (56°F) or above 54°C (130°F). Baro-VNAV and VDP NA when using Mobile Rgnl altimeter setting.

MALS

AS

MISSED APPROACH: Climb to 800 then climbing right turn to 2000 direct WORIR and hold.

ATIS 135.575	MOBILE APP CON ★ 118.5 269.3	DOWNTOWN TOWER ★ 118.8 (CTAF) 251.1	GND CON 121.7 239.3	UNICOM 122.95
------------------------	--	---	-------------------------------	-------------------------

MISSD APCH FIX

4 NM

176°
356°

WORIR

ELEV	26	TDZE	25
------	----	------	----

800

2000

WORIR

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 71).

*LNAV only.

LURDE

1700

ROKGO

4 NM Holding Pattern

*1.3 NM to RW32

1700

320°

140°

1700

GP 3.00° TCH 55

CATEGORY	A	B	C	D
LPV DA	225/18	200 (200-½)		
LNAV/VNAV DA	283/24	258 (300-½)		
LNAV MDA	480/24	455 (500-½)	480/50	455 (500-1)
CIRCLING	680-1	654 (700-1)	680-1¾ 654 (700-1¾)	1100-3 1074 (1100-3)

MOBILE, ALABAMA

Amdt 2A 17AUG17

30°38'N-88°04'W

MOBILE DOWNTOWN (BFM)

RNAV (GPS) RWY 32