

WAAS
CH **86233**
W26A

APP CRS
264°

Rwy Idg
TDZE **176**
Apt Elev **176**

5004

176

176

RNAV (GPS) RWY 26

CAMILLA-MITCHELL COUNTY (CXU)

Baro-VNAV NA when using Albany altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). DME/DME RNP-0.3 NA.

When local altimeter setting not received, use Albany altimeter setting and increase all DA 48 feet and all MDA 60 feet; increase visibility LPV all Cats and LNAV Cats C and D and Circling Cat C ¼ mile and LNAV/VNAV all Cats ½ mile. Helicopter visibility reduction below 1 SM NA.

Rwy 26 Straight-in and Circling minimums NA at night.

MISSED APPROACH:

Climb to 2200 direct CEGUK and hold.

AWOS-3T 118.675	JACKSONVILLE CENTER 125.75 226.8	UNICOM 122.8 (CTAF) 0
---------------------------	--	--

Procedure NA for arrivals at CHULA on V578 eastbound.

MSA RW26 25 NM

2600

370 Δ 580 Δ 1900 Δ 264° (6.1) 4 NM 084° 264° (IF/IAF) CEVOR

2400 NoPT 225° (20) (IAF) CHULA

2400 NoPT 314° (15.9) (IAF) WUBSU

MISSED APCH FIX CEGUK

084° 264° 4 NM

2400 NoPT 314° (15.9) (IAF) WUBSU

ELEV 176	TDZE 176				
		2200 CEGUK	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 39).		
		264° to RW26	CEVOR 4 NM Holding Pattern		
		221±	KUBCE 1900 264° 1900 264° 2400 084°		
		5004 X 100	GP 3.00° TCH 58		
			5.2 NM	6.1 NM	
		CATEGORY	A	B	C D
		LPV DA	505-1		329 (400-1)
		LNAV/VNAV DA	553-1¼		377 (400-1¼)
		LNAV MDA	660-1	484 (500-1)	660-1¾ 484 (500-1¾)
		CIRCLING	720-1	544 (600-1)	720-1½ 544 (600-1½) 760-2 584 (600-2)

CAMILLA, GEORGIA

Amdt 1B 29MAY14

31°13'N-84°14'W

RNAV (GPS) RWY 26

CAMILLA-MITCHELL COUNTY (CXU)