

APP CRS	Rwy Idg	9397
061°	TDZE	7667
	Apt Elev	7680

RNAV (RNP) RWY 6

GUNNISON-CRESTED BUTTE RGNL (GUC)

RF and GPS required. When local altimeter setting not received, procedure NA. For uncompensated Baro-VNAV systems, procedure NA below -29°C (-20°F) or above 54°C (130°F). When VGSJ inoperative, procedure NA at night. Visibility reduction by helicopters NA. Missed approach requires RNP less than 1.0.

* Missed approach requires minimum climb of 310 feet per NM to 9000.

Missed approach requires minimum climb of 260 feet per NM to 9000.

† Missed approach requires minimum climb of 230 feet per NM to 9000.

For inoperative MALSF, increase RNP 0.11* visibility to 1½, RNP 0.20 # to 1¾, RNP 0.26 † to 2, and RNP 0.30 to 2¼.

MALSF

MISSED APPROACH: (Do not exceed 240 KIAS until RNGLE) Climb to 13000 via track 062° to POSLY, and via right turn to JENRO, and via right turn to TIPOC, and via right turn to RNGLE, and via track 306° to HBU VOR/DME and hold.

AWOS-3PT 135.075	DENVER CENTER 124.5 350.25	UNICOM 122.7 (CTAF)
---------------------	-------------------------------	------------------------

Procedure Turn NA

KEEZR

11000

061°

10300

OSDUE

13000

POSLY

JENRO

10300

RW06

6.8 NM

7.5 NM

CATEGORY	A	B	C	D
RNP 0.11 DA*	NA	8125-1¼	458 (500-1¼)	NA
RNP 0.20 DA#	NA	8219-1½	552 (600-1½)	NA
RNP 0.26 DA†	NA	8294-1¾	627 (700-1¾)	NA
RNP 0.30 DA	NA	8354-2	687 (700-2)	NA

ELEV 7680 TDZE 7667

7735 ±

0.3% UP

9400 X 150

7773

0.5% UP

2981 X 150

35

061° to RW06

HIRL Rwy 6-24
REIL Rwy 24

AUTHORIZATION REQUIRED

GUNNISON, COLORADO

Orig-A 30JUN11

38°32'N-106°56'W

GUNNISON-CRESTED BUTTE RGNL (GUC)

RNAV (RNP) RWY 6