


EEONS SEVEN DEPARTURE (RNAV)

ATIS  
120.3  
CLNC DEL  
128.6  
DENVER DEP CON  
132.75 269.3

TOP ALTITUDE:  
FL230

- NOTE: DME/DME/IRU or GPS required.  
NOTE: RNAV 1.  
NOTE: Turbojets only.  
NOTE: RADAR required.  
NOTE: Accelerate to at or above 250K above 10000. If slower speed is required to meet crossing restrictions advise CLNC DEL prior to taxi.



TAKEOFF MINIMUMS

- Rwys 10, 28: NA - ATC.  
Rwys 35L/R: Standard.  
Rwy 17L: Standard with minimum climb of 255' per NM to 8000.  
Rwy 17R: Standard with minimum climb of 370' per NM to 8000.

NOTE: Chart not to scale.



DEPARTURE ROUTE DESCRIPTION

- TAKEOFF RUNWAYS 17L/R: Climb on heading 170° to 6400, then continue climb on heading 170° or as assigned by ATC, thence. . . .  
TAKEOFF RUNWAYS 35L/R: Climb on heading 350° to 6400, then continue climb on heading 350° or as assigned by ATC, thence. . . .  
. . . .RADAR vectors to EEONS, then on depicted route to WYNDM. Maintain FL230 or filed lower altitude, expect higher filed altitude 10 minutes after departure.