

APP CRS
281°

Rwy Idg
TDZE
Apt Elev

11236
13
13

RNAV (GPS) X RWY 28R

SAN FRANCISCO INTL (SFO)

NA

Runway 28L and 28R separated by 750 feet centerline to centerline. DME/DME RNP-0.3 NA. When executing a missed approach or go-around, unless otherwise instructed by ATC, initially turn right to 030° utilizing heading mode. Inoperative table does not apply. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below 2°C (36°F) or above 54°C (130°F).

*If a go-around executed after passing DARNE, go-around requires a minimum climb of 380 feet per NM to 1800.

ALSIF-2

MISSED APPROACH:
Climbing right turn to 3000 on heading 030° then direct OAK VOR/DME and hold.

D-ATIS 113.7 115.8 118.85	NORCAL APP CON 134.5 338.2	SAN FRANCISCO TOWER 120.5 269.1	GND CON 121.8	CLNC DEL 118.2	CPDLC
-------------------------------------	--------------------------------------	---	-------------------------	--------------------------	-------

ELEV 13

TDZE 13

TDZ/CL Rwy's 19L and 28R
REIL Rwy's 1L, 1R, and 10L
HIRL all Rwy's

3000 OAK

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 68).

CATEGORY	A	B	C	D
LNAV/VNAV	DA*	1140-4	1127 (1200-4)	

SAN FRANCISCO, CALIFORNIA

37°37'N-122°23'W

SAN FRANCISCO INTL (SFO)

Amdt 1B 13OCT16

RNAV (GPS) X RWY 28R