


RADAR INSTRUMENT APPROACH MINIMUMS

LEMOORE NAS (KNLC), (REEVES FIELD), CA (Amdt 6, 19311 USN) ELEV 229
RADAR - (E) 125.95 270.8x 314.0x 317.575x 322.45x 323.15x 336.4x 346.375x 348.75x 353.55x
363.7x 370.875x 377.075x 

	RWY	GS/TCH/RPI	CAT	DH/ MDA-VIS	HAT/ HAT _h / HAA	CEIL-VIS
PAR ¹⁴	32L ²⁸	3.0°/40/766	ABCDE	328/16	100	(100-¼)
	14L	3.0°/54/1019	ABCDE	320/24	100	(100-½)
	32R ⁵	3.0°/45/857	ABCDE	322/24	100	(100-½)
	14R ⁵	3.0°/51/979	ABCDE	329/24	100	(100-½)
ASR ⁴	32L ³⁷		ABCDE	540/24	312	(400-½)
	14L		ABCDE	560/55	340	(400-1)
	14R ⁵		AB	640/55	411	(500-1)
			CDE	640/60	411	(500-1⅙)
	32R ⁵		AB	760/55	538	(600-1)
			CDE	760-1½	538	(600-1½)
CIR ⁸	ALL RWYS		AB	680-1	451	(500-1)
			C	680-1½	451	(500-1½)
			DE	780-2	551	(600-2)
CIR ASR	32R		AB	760-1	531	(600-1)
			C	760-1½	531	(600-1½)
			DE	780-2	551	(600-2)

¹No-NOTAM MP: PAR-Rwy 14R-32L 1600-2400Z++ Mon, Rwy 14L-32R 1600-2400Z++ Wed.
²When ALS inop, increase CAT ABCDE RVR to 24 and vis to ½ mile.
³When ALS inop, increase CAT ABCDE RVR to 55 and vis to 1 mile.
⁴Simultaneous approaches authorized.
⁵Pattern at 2800 ft.
⁶Caution: WCH group 4: 15 ft less than required 20 ft.
⁷Step Down Fix at 3 NM from THLD, 1180 min.
⁸Circling authorized only from ASR and PAR w/o GS.

31 DEC 2020 to 28 JAN 2021

31 DEC 2020 to 28 JAN 2021