

APP CRS
016°

Rwy Idg
TDZE
Apt Elev

5701
56
56

RNAV (GPS) Y RWY 2L

JOHN WAYNE AIRPORT-ORANGE COUNTY (SNA)

DME/DME RNP-0.3 NA. VDP NA when using Fullerton altimeter setting. When local altimeter setting not received, use Fullerton altimeter setting and increase all MDA 40 feet, increase Circling Cat C visibility ¼ SM.

MISSED APPROACH: Climb to 800 then climbing left turn to 2600 direct SLI VORTAC and hold.

D-ATIS 126.0	SOCAL APP CON 121.3 263.1	JOHN WAYNE TOWER ★ 126.8 (CTAF) 0 343.625	GND CON (EAST) 120.8 (WEST) 132.25	CLNC DEL 118.0	CPDLC	UNICOM 122.95
------------------------	-------------------------------------	--	--	--------------------------	-------	-------------------------

VGSI and descent angles not coincident (VGSI Angle 3.00/TCH 72).

MINOE

NEWPO

WUNAD 2 NM to RW02L

SLI

3000

1600

740

800

2600

016°

3.00°

1.2 NM to RW02L

0.8 NM

1.2 NM

6.4 NM

2.7 NM

0.8 NM

1.2 NM

016° to RW02L

REIL Rwy 20L

MIRL Rwy 2R-20L

HIRL Rwy 2L-20R

CATEGORY	A	B	C	D
LNNAV MDA	520-1 464 (500-1)		520-1⅜ 464 (500-1⅜)	
CIRCLING	640-1 584 (600-1)		840-2¼ 784 (800-2¼)	1160-3 1104 (1200-3)

SANTA ANA, CALIFORNIA

JOHN WAYNE AIRPORT-ORANGE COUNTY (SNA)

Amdt 2 10NOV16

33°41'N-117°52'W

RNAV (GPS) Y RWY 2L