RNAV (GPS) X RWY 24

MC CLELLAN-PALOMAR (CRQ)

WAAS	APP CRS	Rwy Idg	4897
CH 45831	245°	TDZE	326
W24B		Apt Elev	331

T A For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -4°C (25°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. RF required. Rwy 24 helicopter visibility reduction below RVR 4000 NA. For inop ALS, increase LNAV/VNAV all Cats visibility to 1⅞ SM. Increase LNAV Cats A/B visibility to RVR 5500, Cat C to 1⅞ SM. Inop table does not apply to LPV.

MALSR

MISSED APPROACH: Climb to 2000 direct IBUGE and hold.

ATIS	SOCAL APP CON	PALOMAR TOWER★	GND CON	CLNC DEL
120.15	127.3 323.0	118.6 (CTAF) L 276.4	121.8	134.85



ELEV 331 D TDZE 326





CATEGORY	A	B	C	D
LPV DA	528/40 202 (200-¾)		576/40 250 (300-¾)	NA
LNAV/VNAV DA	927-1½ 601 (600-1½)			NA
LNAV MDA	1000/40 674 (700-¾)		1000-1½ 674 (700-1½)	NA
C CIRCLING	1000-1 669 (700-1)	1020-1 689 (700-1)	1260-2¾ 929 (1000-2¾)	NA

REIL Rwy 24 L
HIRL Rwy 6-24 L

SW-3, 31 DEC 2020 to 28 JAN 2021
SW-3, 31 DEC 2020 to 28 JAN 2021