

WAAS CH 97320 W26A	APP CRS 255°	Rwy Idg TDZE Apt Elev	4858 636 652
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 26R

CHINO (CNO)

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 47°C (116°F). DME/DME RNP- 0.3 NA.
Helicopter visibility reduction below ¾ SM not authorized.

MISSED APPROACH: Climb to 4000 direct IRUYI and via 241° track to LAHAB and hold.

ATIS 125.85	SOCAL APP CON 135.4 318.2	CHINO TOWER ★ 118.5 (CTAF)	GND CON 121.6	UNICOM 122.95
-----------------------	-------------------------------------	--------------------------------------	-------------------------	-------------------------

ELEV 652	TDZE 636
----------	----------

		4000	IRUYI	LAHAB	CAZBY	4 NM Holding Pattern		
*LNAV only.		↑	tr 241°	DEWEYE	LINDN			
*1.8 NM to RW26R		255°	2100	3000	256°	4400		
1.8		2.6 NM	3.1 NM	5.9 NM		GP 3.00° TCH 51		
CATEGORY	A	B	C	D				
LPV DA	1030-1¼ 394 (400-1¼)							
LNAV/VNAV DA	1177-2 541 (600-2)							
LNAV MDA	1260-1	624 (700-1)	1260-1¾ 624 (700-1¾)	1260-2	624 (700-2)			
CIRCLING	1260-1¾	608 (700-1¾)		1260-2	608 (700-2)			

CHINO, CALIFORNIA

Orig-D 10DEC15

33°58'N-117°38'W

RNAV (GPS) RWY 26R

CHINO (CNO)