SALT LAKE FOUR DEPARTURE

(SLC4.TCH) 17AUG17

SALT LAKE CITY, UTAH

SALT LAKE CITY INTL (SLC)

D-ATIS
124.75 125.625
CLNC DEL
127.3 379.975
CPDLC
SALT LAKE CITY DEP CON
128.6 322.3

TOP ALTITUDE: 10000

NOTE: RADAR required.
NOTE: This is a RADAR vector departure to assigned route or fix.

TAKEOFF MINIMUMS
Rwys 14, 16R, 16L, 17: Assigned heading 163°, standard with minimum climb of 260′ per NM to 6000. Assigned heading 283° CW 343°, standard with minimum climb of 400′ per NM to 8300.
Rwy 32: Assigned heading 263° CW 343° standard with minimum climb of 498′ per NM to 7800 or 400-1 with minimum climb of 260′ per NM to 7800.
Rwys 34L, 34R, 35: Assigned heading 263° CW 322°, standard with minimum climb of 260′ per NM to 7800. Assigned heading 323° CW 343°, standard with minimum climb of 260′ per NM to 7800.

(NARRATIVE ON FOLLOWING PAGE)

TWIN FALLS
115.8 TWF
Chan 105
N42°28.79′-W114°29.37′
L-11, H-3

MALAD CITY
117.4 MLD
Chan 121
N42°11.99′-W112°27.07′
L-11, H-3

ROCK SPRINGS
116.0 OCS
Chan 107
N41°35.41′-W109°00.92′
L-11, H-3

WASATCH
116.8 TCH
Chan 115
N40°51.02′-W111°58.91′
L-9-11, H-3

MYTON
112.7 MTU
Chan 74
N40°08.95′
W110°07.62′
L-9-11, H-3

FAIRFIELD
116.6 FFU
Chan 113
N40°16.49′-W111°56.43′
L-9-11, H-3

GRAND JUNCTION
112.4 JNC
Chan 71
N39°03.57′-W108°47.55′
L-9, H-3

DELTA
116.1 DTA
Chan 108
N39°18.13′-W112°30.33′
L-9, H-3

R-6404C
R-6404A
R-6404B/D
R-6406A
R-6403
R-6407
R-6402A/B
R-6405
R-6412 A/B
R-6412 C/D

R-340 R-341 R-069 R-070 R-150 R-151 R-175 R-176 R-239 R-240 R-249 R-270 R-269 R-350 R-351 R-110 R-111 R-160

283° 313° 314° 323° 343° 161° 163° 340° 160°

TCH R-161

7500

MINIMUM CROSSING ALTITUDES AT TCH
R-070 CW R-150: 11400′
R-151 CW R-175: 8200′
R-176 CW R-239: 9900′
R-341 CW R-069: 10400′

MINIMUM CROSSING ALTITUDES AT FFU
R-351 CW R-110: 12500′
R-270 CW R-350: 11600′

N

NOTE: Chart not to scale.

(SLC4.TCH) 19283

SALT LAKE FOUR DEPARTURE

AL-365 (FAA)

SALT LAKE CITY INTL (SLC)

SALT LAKE CITY, UTAH